



CAST LED Mini Wash Light Product Information (CWL6CB, CWL6LED1 with Mounting Options)

CAST LED Mini Wash Light Series - Compact, Rugged, Versatile, & Energy Efficient



CWL6LED1
+ CWL9KIT

CWL6LED1 +
CWL9EXKIT



CWL6CB
CWL6LED1

CWL6LED1 +
CWL7KIT



CWL6LED1
+ CWL8KIT

Description:

LED wash lights with body constructed of solid bronze with a variety of canopy and stake-mounted options.

Features:

- ▶ Solid construction, highly corrosion resistant, naturally weathers to a beautiful patina.
- ▶ Available in three standard configurations, with options for custom-height (fixed and telescopic) stems.
- ▶ Enclosed, water-tight LED housing includes internal reflector and frosted glass lens for wide even light distribution (no hot spots) and protection from sprinklers and rain.
- ▶ Warm white (2,801^o K) replaceable integrated LED.
- ▶ Engineered for superior thermal management even in hot humid environments.
- ▶ Pre-wired with 25' tin-coated No-Ox[®] marine grade wire.
- ▶ 60,500 hr. LED life with minimal lumen degradation. Accepts 10V to 24V AC input.

Uses:

Ideal for applications where a wide diffuse beam is needed to illuminate walls, walkways, stairs, and plant material.

Construction:

Solid bronze bodies and canopies; Eurometal stakes; copper brackets and stems; frosted soda lime lens, stainless steel thumbscrews, 25' tin-coated #18-2 No-Ox[®] marine-grade wire.

Dimensions: (CWL6CB or CWL6LED1 with following kits)

CWL6CB, CWL6LED1: 2.5" tall x 6.5" wide

CWL7KIT: 4.0" tall x 6.5" wide*

CWL8KIT: 7.0" tall x 6.5" wide (includes 4.5" stem and 8.5" stake)*

CWL9KIT: 20.5" tall x 6.5" wide (includes 18" stem and 13.5" stake)*

CWL9EXKIT: 21"-36" tall x 6.5" wide (includes extendable stem and 13.5" stake)*

*Custom stem lengths available for all models.

LED Specification Summary:

LED Light Source: Life (L70) 60,500hrs., Color Temp: 2801^oK, CRI: 82, Input Voltage: 10-24 V AC or DC, Power Amps: .47, Watts 5.01, Power Factor .9, Volt Amps 5.57, Lumen Output-Fixture: 122